

RESEARCH Open Access

Bio-ethanol production through simultaneous saccharification and co-fermentation (SSCF) of a low-moisture anhydrous ammonia (LMAA)-pretreated napiegrass (*Pennisetum purpureum* Schumach)

Masahide Yasuda^{1*}, Hayato Nagai¹, Keisuke Takeo¹, Yasuyuki Ishii² and Kazuyoshi Ohta³

Abstract

Efficient bio-ethanol production from napiegrass (*Pennisetum purpureum* Schumach) was investigated. A low-moisture anhydrous ammonia (LMAA)-pretreated napiegrass was subjected to simultaneous saccharification and co-fermentation (SSCF), which was performed at 36°C using *Escherichia coli* KO11, *Saccharomyces cerevisiae*, cellulase, and xylanase. It was found that use of xylanase as well as the LMAA-pretreatment was effective for the SSCF. After the SSCF for 96 h, the ethanol yield reached 74% of the theoretical yield based on the glucan (397 mg g⁻¹) and xylan (214 mg g⁻¹) occurring in dry powdered LMAA-pretreated napiergrass.

Keywords: Bio-ethanol; Simultaneous saccharification and co-fermentation (SSCF); Napiergrass; Cellulase; Xylanase; *Escherichia coli* KO11; LMAA-pretreatment

Introduction

Bioethanol from lignocellulosic biomass has been recognized as one of promising sustainable energy source alternative to petroleum-based fuels, since the lignocelluloses are not directly in competition with food sources (Galbe and Zacchi 2007; Taherzadeh and Karimi 2007). We are interested in ethanol production from herbaceous lignocellulosic napiergrass (*Pennisetum purpureum* Schumach) because of its low lignin content and high harvest amount per year and per area (Yasuda et al. 2012, 2013). In lignocellulosic ethanol production, pentose fermentation is an unavoidable process because of its high xylan content. In pentose fermentation process, however, ethanol concentration is usually too low (<10 g L⁻¹) to distillate with low energy cost. Therefore, pentose fermentation has been performed as co-fermentation of hexose and pentose using a variety of recombinant strains such as Escherichia coli KO11 (Ohta et al. 1990, 1991; Underwood et al. 2002; Brandon et al. 2011), Saccharomyces cerevisiae 424A (LNH-ST) (Jin et al. 2012a, b), S. cerevisiae TMB3400 (Ohgren et al. 2006; Matsushika et al. 2009), and Zymomonas mobilis AX101 (Su et al. 2012). Simultaneous saccharification and co-fermentation (SSCF) is generally superior to the separate saccharification and co-fermentation since SSCF can achieve saccharification, hexose fermentation, and pentose fermentation in one-pot reaction. Here, we applied SSCF to ethanol production from napiergrass, which was treated by low-moisture anhydrous ammonia (LMAA) pretreatment.

Materials and methods

Napiergrass as lignocellulosic materials

As raw material, a dwarf type of napiergrass was cultivated in the Kibana Agricultural Science Station, at the University of Miyazaki. Leaf blades of the napiergrass were separated from the stem and then cut by a cutter and dried at 70°C for 72 h. The dried matter was ground until 70% of the particles were in a range of 32–150 μm in length.

¹Department of Applied Chemistry, Faculty of Engineering, University of Miyazaki, Gakuen-Kibanadai Nishi, Miyazaki 889-2192, Japan Full list of author information is available at the end of the article



^{*} Correspondence: yasuda@cc.miyazaki-u.ac.jp

Chemical components of napiergrass

The powdered napiergrass (30 g) was treated with a 1% aqueous solution of NaOH (400 mL) at 95°C for 1 h. The holocellulose was isolated as a pale yellow precipitate by centrifugation and filtration of the treated mixture. The supernatant solution was neutralized to pH 5.0 by a dilute HCl solution. The resulting dark brown precipitate identified as lignin was collected via centrifugation at 10,000 rpm for 10 min. Sugars in holocellolose were determined according to the methods published by the National Renewable Energy Laboratory as follows (Sluiter et al. 2010). Sulfuric acid (72 wt%, 3.0 mL) was added slowly to holocelulose (300 mg) and kept at 30°C for 1 h. The resulting solution was diluted by water (84 mL) until the concentration of sulfuric acid was 4 wt%. Acid hydrolysis was performed by autoclaving at 121°C for 1 h in an autoclave. After the neutralization by CaCO₃, the solution was subjected to the centrifugation to give the supernatant solution (ca. 87 mL), which was concentrated to 30 mL by evaporation. The solution was analyzed by HPLC. The peaks of glucose and xylose appeared whereas the peaks of galactose and arabinose were very weak because of their low contents. The amounts of glucan and xylan were determined from the amounts of glucose and xylose determined by HPLC. It was confirmed that the sum amounts of glucan and xylan were equaled to the amounts of hollocellolose. The ash component in lignocellulose was obtained by the burning of the lignocellulose (2.0 g) in an electric furnace (KBF784N1, Koyo, Nara, Japan) for 2 h at 850°C.

Low-moisture anhydrous ammonia (LMAA) pretreatment

Water (100 g) was added dropwise to dry powdered napiergrass (100 g, volume 320 mL) in the flask (1 L). The resulting moist powdered napiergrass in the flask was evacuated with a pump under 20 mm Hg and then gaseous NH₃ was introduced into the flask. This operation was performed three times until the atmosphere inside the flask was entirely replaced with NH₃. The amount of NH₃ presented in the flask was 1.1 g. The LMAA pretreatment was performed by modifying the Kim method where LMAA pretreatment was performed at 80°C for 86 h (Yoo et al. 2011). In our LMAA-pretreatment, the moist powdered napiergrass was kept under NH3 gas atmosphere at room temperature for four weeks (28 days). After the treatment, the NH₃ was removed with an evaporator. The treated napiergrass was washed with water (2 L) three times to separate the brownish aqueous solution of the lignin. After pH was checked to be neutral, the pretreated napiergrass was dried at 60°C to weigh out the precise amount of napiergrass in the following biological treatment.

Hydrolytic enzyme for saccharification

A cellulase from *Acremonium cellulolyticus* (Acremozyme KM, Kyowa Kasei, Osaka, Japan) was selected by

comparing its activity with other cellulases such as Meycellase (Meiji Seika), a cellulase from *Trichoderma viride* (Wako Chemicals, Osaka, Japan) and a cellulase from *Aspergillus niger* (Fluka Japan, Tokyo) (Yasuda et al. 2011). The cellulase activity of Acremozyme KM was determined to be 1,320 units mg⁻¹ by the method of breaking down filter paper (Kitamikado and Toyama 1962). A xylanases from *Trichoderma longibrachiatum (reesei)* (Sumizyme X, Shin Nihon Chemicals, Anjyo, Japan, 5,000 u g⁻¹) was selected from commercially available hemicellulase.

Saccharification was performed for the powdered napiergrass (10.0 g) using both cellulase and xylanase, whose total amount was 1.0 g, at 45°C in an acetate buffer (60 mL, pH 5.0).

Preparation of the inoculum culture of *Escherichia coli* KO11 and *Saccharomyces cerevisiae*

E. coli KO11 was grown in the LB medium (200 mL) consisting of tryptone (2.0 g L⁻¹, Difco), yeast extract (1.0 g L⁻¹), and NaCl (2.0 g L⁻¹) under shaking at 150 rpm at 37°C for 24 h. The KO11 cell suspension contained a dry weight of 0.52 mg mL⁻¹ of *E. coli* KO11. *Saccharomyces cerevisiae* NBRC 2044 was grown at 30°C for 24 h in a basal medium (initial pH 5.5) consisting of glucose (20.0 g L⁻¹), polypeptone (1.0 g L⁻¹), yeast extract (1.0 g L⁻¹), KH₂PO₄ (1.0 g L⁻¹), and MgSO₄ (3.0 g L⁻¹). After incubating for 24 h, the cell suspension of *S. cerevisiae*, whose grown culture of *S. cerevisiae* showed a cell density of 7.7×10^7 cells mL⁻¹, was obtained (Yasuda et al. 2012).

Simultaneous saccharification and co-fermentation (SSCF)

Typical procedure of SSCF is as follows. The LMAApretreated napiergrass (3.0 g) was suspended in the acetate buffer (14.0 mL, pH 5.0) and then autoclaved at 121°C for 20 min. After cooling to room temperature under UVirradiation, the cell suspension (0.36 mL) of S. cerevisiae, a portion (21 mL) of the inoculum culture E. coli KO11, and the cellulase (150 mg) and xylanase (150 mg) in an acetate buffer solution (5.0 mL, pH 5.0) were added to the suspension of the napiergrass. After pH was adjusted to 6.0, air was purged with N2. In the SSCF without S. cerevisiae, replacement by N₂ gas was not performed. The SSCF was initiated by stirring the solution vigorously with a magnetic stirrer at 36°C which was an optimal fermentation temperature of E. coli KO11. The evolved CO2 was collected over water by a measuring cylinder, and the reaction was monitored by the volume of CO₂. The SSCF reaction was continued for 96 h until CO2 evolution ceased.

Analytical methods

Saccharides were analyzed on a high-performance liquid chromatography system (LC-20AD, Shimadzu, Kyoto,

Japan) equipped with RI detector (RID-10A) using an anion exchange column (NH2P-50 4E; Shodex Asahipak, 250 mm in length and 4.6 mm in ID, Yokohama, Japan). Acetonitrile-water (8:2 v/v) was flowed at 1.0 mL min⁻¹ as mobile phase. Ethanol was analyzed by gas-liquid chromatography using 2-propanol as an internal standard on a Shimadzu gas chromatograph GC-8A equipped with a glass column of 5% Thermon 1000 on Sunpak-A (Shimadzu).

Results and discussion

Ethanol production from lignocelluloses

In general, the cellulosic bio-ethanol production involves three steps such as saccharification of cellulosic components (SA), hexose fermentation (HF), and pentose fermentation (PF). These processes are combined each other to simplify the procedure and enhance the ethanol yield. Typical combinations are as follows: SSF is simultaneous process of SA and HF but does not take place PF. CF is co-fermentation of hexose and pentose. SSCF is simultaneous process of SA, HF, and PF. For efficient cellulosic bio-ethanol production, moreover, pretreatment to remove the lignin and/or promote an enzymatic digestibility of the cellulosic components are usually required.

Napiergrass as raw material

Napiergrass belongs to herbaceous tropical species, native to the east Africa and has high dry matter productivity with moderate forage quality in southern Kyushu (Ishii et al. 2005a, 2013). Napiergrass has wide variation of phenotypes, reflected by plant breeding due to the crossing of dwarf genotype and relative species such as pearl millet (Pennisetum americanum) (Ishii et al. 2005a; Hanna and Sollenburger 2007). A dwarf variety of late-heading type of napiergrass (dwarf napiergrass) originated from Florida, USA, via Thailand (Mukhtar et al. 2003) was assessed to be suitable for both grazing (Ishii et al. 2005b) and cutand-carry systems among several sites of southern Kyushu, Japan (Utamy et al. 2011). Dwarf napiergrass meets the requirement of lignocellulose for the biofuel production because it has low lignin-content and a relatively high herbage mass per year and per area (Rengsirikul et al. 2011; Rengsirikul et al. 2013; Khairani et al. 2013). Therefore, we have continued to use this dwarf type of napiergrass for the bio-ethanol (Yasuda et al. 2011) and biohydrogen production (Shiragami et al. 2012).

As has been reported previously (Yasuda et al. 2013), the LMAA-pretreatment was useful for the simultaneous saccharification and fermentation (SSF) of napiergrass. In the present case, therefore, the powdered napiergrass was subjected to the LMAA-pretreatment. The LMAA-pretreated napiergrass contained 39.7 wt% of glucan, 21.4 wt% of xylan, 7.1 wt% of lignin, and 7.1 wt% of ash,

while the components of the non-treated napiergrass were determined to be 31.3 (glucan), 16.9 (xylan), 12.6 (lignin), and 13.9 wt% (ash).

Optimization of enzymatic saccharification

The effect of LMAA-pretreatment was checked by the enzymatic saccharification. Saccharification of non-treated and LMAA-pretreated napiergrass (10.0 g) was performed using cellulase (Acremozyme KM, 1.00 g) at 45°C in an acetate buffer (60 mL). Results are shown in Table 1. Saccharification of no-treated napiergrass produced the total saccharides in 54% yield (Table 1 run 1). In the case of napiergrass which was subjected LMAA pretreatments for four weeks, the yield of saccharides was 67% which was the higher than the cases of LMAA for one and two weeks (runs 2–4). Figure 1 shows the time-conversion of glucose and xylose obtained from the saccharification of the LMAA-pretreated napiergrass. Although the glucose increased rapidly to reach the maximum amounts until 48 h, xylose increased gradually even at saccharification for 360 h. Thus the saccharification of xylan was very slow.

In order to shorten the saccharification time, xylanase (Sumizyme X) was used in addition to cellulase. Xylanase was used in $F_X \times 1.0$ g where F_X was a fraction of xylanase in the mixed enzymes. Figure 2 shows the effect of F_X on the saccharide yields in the saccharification of LMAA-pretreated napiergrass for 168 h. The optimal F_X value was determined to be 0.50 since the yield of xylose was

Table 1 Saccharification of LMAA-pretreated napiergrass^{a)}

			-	-	_
Run	PT ^{b)}	$F_{X}^{c)}$	Pro	%) ^{d)}	
			Glucose	Xylose	Total
1	NO	0.0	2.20 (63)	0.68 (36)	2.88 (54)
2	LMAA (1)	0.0	2.89 (66)	0.91 (38)	3.80 (63)
3	LMAA (2)	0.0	3.07 (70)	1.16 (49)	4.23 (63)
4	LMAA (4)	0.0	3.36 (76)	1.20 (51)	4.57 (67)
5	LMAA (4)	0.3	3.23 (73)	1.13 (48)	4.36 (64)
6	LMAA (4)	0.4	3.56 (81)	1.49 (63)	5.05 (74)
7	LMAA (4)	0.5	4.14 (94)	1.60 (68)	5.74 (85)
8	LMAA (4)	0.6	4.25 (96)	1.48 (62)	5.73 (86)
9	LMAA (4)	0.7	3.92 (90)	1.51 (64)	5.43 (81)
10	LMAA (4)	0.8	3.72 (84)	1.47 (62)	5.20 (78)
11	LMAA (4)	0.9	3.63 (82)	1.30 (55)	4.93 (73)
12	LMAA (4)	1.0	3.05 (69)	0.95 (40)	4.00 (59)

 $^{^{\}rm a)}$ Saccharification was performed for napiergrass (10.0 g) using the hydrolytic enzyme (1.0 g) in an acetate buffer (60 mL) at 45°C for 168 h.

^{b)}Pretreatment (PT). NO: non-treatment. LMAA: a low-moisture anhydrous ammonia pretreatment. The value in parenthesis was the period in week for LMAA- pretreatment.

 $^{^{\}rm c)}F_{\rm X}$ value was the fraction of xylanase in the mixture (1.0 g) of cellulase and xylanase.

^{d)}The amounts of saccharides obtained from the saccharification of 10 g of the pretreated napiergrass.




Figure 1 Time-conversion plots of the amounts of glucose and xylose in saccharification of LMAA-pretreated napiergrass (10.0 g) using cellulase and/or xylanase. Glucose (\spadesuit) and xylose (\triangle) from the saccharification using cellulase (0.50 g) and xylanase (0.50 g). Glucose (\diamondsuit) and xylose (\triangle) from the saccharification using only cellulase (1.0 g).

maximum. Under optimized conditions where the saccharification was performed for the LMAA-pretreated napiergrass (10.0 g) by a mixture of enzymes, cellulase (0.50 g) and xylanase (0.50 g), the yields of glucose and xylose reached 94% and 68%, respectively (run 7). Moreover, the addition of xylanase shortened the saccharification time of xylan to 168 h, as shown in Figure 1.

SSCF of the LMAA-pretreated napiergrass

The results of SSCF were listed in Table 2. The ethanol yield was 43% in the SSCF of non-treated napiergrass using S. cerevisiae, E. coli KO11, cellulase and xylanase, (Table 2, run 1). The LMAA-pretreatment enhanced the ethanol yield (runs 2-3). The amount of napiergrass was optimized to be 3.0 g from the comparison of ethanol yields in the cases of 2.5 to 4.0 g (runs 5-7). Maximum ethanol yield was 74% in SSCF of LMAA-pretreated napiergrass using S. cerevisiae, E. coli KO11, cellulase, and xylanase for 96 h (run 2). The ethanol yield was not changed even though SSCF time was elongated until 168 h when the xylose yield reached the maximum yield in saccharification process. In the case of SSCF without S. cerevisiae (run 3), the ethanol yield was 70%. If the glucan (1.191 g) occurring in the LMAA-pretreated napiergrass (3 g) is completely turned to ethanol, 676 mg of ethanol will be produced. Ethanol amounts of SSCF in runs 2 and 3 exceeded this value (676 mg), showing that the pentose fermentation apparently occurred. Moreover, the ethanol amount (777 mg, run 2) was comparable to the ethanol amount (880 mg) which was ethanol amount when glucose and xylose produced by enzymatic saccharification (Table 1 run 7) would be completely fermented. Therefore, it was suggested that yields of hexose and pentose fermentations were moderately high.

The additive effect of Saccharomyces cerevisiae

S. cerevisiae is the most commonly used microorganism for industrial ethanol production. However, it cannot utilize xylose for growth and ethanol production. Therefore, it is requisite to use a recombinant species which can ferment pentose. In our SSCF process, S. cerevisiae was used in addition to a recombinant E. coli KO11 for fermentation, since it was found that the SSCF using four components (S. cerevisiae, E. coli KO11, cellulase, and xylanase) proceeded slightly faster than the SSCF without S. cerevisiae.

Figure 3 shows time conversions of ethanol, glucose, and xylose in SSCF. The ethanol yield increased gradually until the yield reached 50% which was comparable to the SSF yield (55%) using *S. cerevisiae*, cellulase and xylanase (Table 2, run 4). At that time, the glucose was completely fermented due to the fast glucose formation




Figure 2 The effects of the fraction of xylanase (F_X) on the yields of glucose (\diamondsuit) and xylose (\blacktriangle) . The saccharification of LMAA-pretreated napiergrass (10.0 g) was performed for 168 h using a mixed enzyme of cellulase and xylanase.

Table 2 SSCF of LMAA-treated napiergrass^{a)}

No	Napiergrass		Enzyme/	KO11/	Yeast/	Products/mg (Yield/%) ^{b)}			Ethanol/
	PT ^{c)}	Weight/g	mg ^{d)}	mL ^{e)}	mL ^{f)}	Xylose	Glucose	Ethanol	gL ^{-1 h)}
1 ⁱ⁾	NO	3.0	300	21	0.36	209 ± 14 (35)	19 ± 2 (2)	353 ± 31 (43)	8.8
2	LMAA	3.0	300	21	0.36	73 ± 25 (10)	$47 \pm 10 (4)$	777 ± 15 (74)	19.4
3	LMAA	3.0	300	21	0	148 ± 11 (20)	43 ± 2 (3)	731 ± 12 (70)	18.3
4 ^{j)}	LMAA	3.0	300	0	0.36	473 ± 43 (65)	29 ± 10 (2)	576 ± 39 (55)	14.4
5	LMAA	2.5	250	21	0.36	304 ± 15 (50)	$37 \pm 6 (3)$	547 ± 41 (63)	13.7
6	LMAA	3.5	350	21	0.36	$385 \pm 45 (53)$	$37 \pm 2 (3)$	719 ± 13 (59)	18.1
7	LMAA	4.0	400	21	0.36	438 ± 37 (60)	$39 \pm 8 (3)$	829 ± 28 (60)	21.4

a)SSCF was performed for napiergrass (3.0-4.0 g) using cellulase (150-200 mg) and xylanase (150-200 mg) in buffer (19 mL), E. coli KO11 (21 ml), and S. cerevisiae (0.36 mL) at 36°C for 96 h. The data were expressed as averages of the experiments at three times.

b) The maximum amounts of xylose, glucose, and ethanol were 729 mg, 1323 mg, and 1049 mg obtained from 3.0 g of LMAA-pretreated napiergrass, respectively.

c)Pretreatment (PT). NO: non-treatment. LMAA: a low-moisture anhydrous ammonia pretreatment for four weeks.

d)Weight of total hydrolytic enzyme (cellulase and xylanase) in mg. The fraction (F_X) of xylanase in the mixture of cellulase and xylanase was 0.50.


e)Volume of the cell suspension of *E. coli* KO11 in ml.


 $^{^{\}mbox{\scriptsize f)}}\mbox{Volume}$ of the cell suspension of S. cerevisiae in mL.

 $^{^{\}text{h})}$ Concentration of ethanol in g L $^{\text{-1}}$.

ⁱⁱThe maximum amounts of xylose, glucose, and ethanol obtained from non-treated napiergrass (3.0 g) were 576 mg, 1043 mg, and 827 mg, respectively.

The simultaneous saccharification and fermentation (SSF) using cellulase (150 mg) and xylanase (150 mg), and S. cerevisiae (0.36 mL) at 36°C for 96 h.





in the saccharification while the xylose was accumulated due to slow fermentation of xylose. After SSCF for 18 h, the xylose fermentation started, resulting in that ethanol yield increased again.

Conclusions

We have previously examined ethanol formation through a combination of SSF using enzyme and S. cerevisiae with a pentose fermentation using E. coli KO11. The ethanol yields from LMAA-pretreated and non-treated napirgrass were 69% (Yasuda et al. 2013) and 44% (Yasuda et al. 2012), respectively. The present SSCF process improved the ethanol yield to 74%. Mass balance of the present SSCF is summarized in Figure 4. Consequently 25.9 g of ethanol was produced from 100 g of LMAA-pretreated napiergrass which was obtained from 127 g of the nontreated powdered napiergrass. Since the SSCF can be performed in one-pot reaction, it can prevent contamination risks of other micro-organism and can construct simple processing procedure. Thus, efficient bio-ethanol production from napiergrass was successfully achieved by the combination of the LMAA-pretreatment with the SSCF process using four components (cellulase, xylanase, Saccharomyces cerevisiae, and E. coli KO11).

Competing interests

The authors declare that they have no competing interests.

Authors' contributions

MY conceived experimental idea involving LMAA-pretreatment and SSCF and analyzed experimental data. Also MY prepared the manuscript and revised it. HN and KO carried out fermentation process using *E. coli* KO11. KT carried out LMAA-pretreatment and saccharification processes. YI developed dwarf type of napiergrass and provided raw material. All authors read and approved the final manuscript.

Acknowledgments

We sincerely thank Lonnie O. Ingram from the University of Florida for providing the *E. coli* KO11 strain. This study was done as a part of the project entitled "Research and Development of Catalytic Process for Efficient Conversion of Cellulosic Biomass into Biofuels and Chemicals (2009–2013)" through Special Funds for Education and Research from the Ministry of Education, Culture, Sports, Science, and Technology of Japan.

Author details

¹Department of Applied Chemistry, Faculty of Engineering, University of Miyazaki, Gakuen-Kibanadai Nishi, Miyazaki 889-2192, Japan. ²Department of Animal and Grassland Sciences, Faculty of Agriculture, University of Miyazaki, Gakuen-Kibanadai Nishi, Miyazaki 889-2192, Japan. ³Department of Biochemistry and Applied Biosciences, Faculty of Agriculture, University of Miyazaki, 1-1 Gakuen-Kibanadai Nishi, Miyazaki 889-2192, Japan.

Received: 18 May 2014 Accepted: 23 June 2014 Published: 1 July 2014

References

- Brandon SK, Sharma LN, Hawkins GM, Anderson WF, Chambliss CK, Doran-Peterson J (2011) Ethanol and co-product generation from pressurized batch hot water pretreated T85 bermudagrass and Merkeron napiergrass using recombinant *Escherichia coli* as biocatalyst. Biomass Bioenergy 35:3667–3673
- Galbe M, Zacchi G (2007) Pretreatment of lignocellulosic materials for efficient bioethanol production. Adv Biochem Eng Biotechnol 108:41–65
- Hanna WW, Sollenberger LE (2007) Tropical and Subtropical Grasses. In: Barnes RF (ed) Forages, vol II, 6th edn. Blackwell Pub, Iowa USA, pp 245–255

- Ishii Y, Yamaguchi N, Idota S (2005a) Dry matter production and *in vitro* dry matter digestibility of tillers among napiergrass (*Pennisetum purpureum* Schumach) varieties. Grassl Sci 51:153–163
- Ishii Y, Mukhtar M, Idota S, Fukuyama K (2005b) Rotational grazing system for beef cows on dwarf napiergrass pasture oversown with Italian ryegrass for 2 years after establishment. Grassl Sci 51:209–220
- Ishii Y, Hamano K, Kang DJ, Rengsirikul K, Idota S, Fukuyama K, Nishiwaki A (2013) C₄-Napier grass cultivation for cadmium phytoremediation activity and organic livestock farming in Kyushu, Japan. J Agric Sci Techn A 3:321–330
- Jin M, Gunawan C, Balan V, Lau MW, Dale BE (2012a) Simultaneous saccharification and co-fermentation (SSF) of AFEX™ pretreated corn stover for ethanol production using commercial enzymes and Saccharimyces cerevisiae 424A (LNH-ST). Bioresour Technol 110:587–594
- Jin M, Gunawan C, Balan V, Yu X, Dale BE (2012b) Continuous SSF and AFEX™ pretreated corn stover for enhanced ethanol productivity using commercial enzymes and *Saccharimyces cerevisiae* 424A (LNH-ST). Biotechnol Bioengineer 110:1302–1311
- Khairani L, Ishii Y, Idota S, Utamy RF, Nishiwaki A (2013) Variation in growth attributes, dry matter yield and quality among 6 genotypes of Napier grass used for biomass in year of establishment in southern Kyushu. Asian J Agric Res 7:15–25
- Kitamikado T, Toyama N (1962) An assay method for cellulase based on the breakdown of filter paper. Hakkoukougakuzasshi 40:85–88
- Matsushika A, Inoue H, Kodaki T, Sawayama S (2009) Ethanol production from xylose in engineered *Saccharomyces cerevisiae* strains: current state and perspectives. Appl Micorobiol Biotechnol 84:37–53
- Mukhtar M, Ishii Y, Tudsri S, Idota S, Sonoda T (2003) Dry matter productivity and overwintering ability in the dwarf and normal napiergrasses as affected by the planting density and cutting frequency. Plant Prod Sci 6:65–73
- Ohgren K, Bengtsson O, Gorwa-Grauslund MF, Galbe M, Hahn-Hagerdal B, Zacchi G (2006) Simultaneous saccharification and co-fermentation of glucose and xylose in steam-pretreated corn stover at high fiber content with Saccharomyces cerevisiae TMB3400. J Biotechnol 126:488–498
- Ohta K, Alterthum F, Ingram LO (1990) Effects of environmental conditions on xylose fermentation by recombinant *Escherichia coli*. Appl Environ Microbiol 56:463–465
- Ohta K, Beall DS, Mejia JP, Shanmugam KT, Ingram LO (1991) Genetic improvement of *Escherichia coli* for ethanol production: chromosomal integration of *Zymomonas mobilis* genes encoding pyruvate decarboxylase and alcohol dehydrogenase II. Appl Environ Microbiol 57:893–900
- Rengsirikul K, Ishii Y, Kangvansaichol K, Pripanapong P, Sripichitt P, Punsuvon V, Vaithanomsat P, Nakamanee G, Tudsri S (2011) Effects of inter-cutting interval on biomass yield, growth components and chemical composition of napiergrass (Pennisetum purpureum Schumach) cultivars as bioenergy crops in Thailand. Grassl Sci 57:135–141
- Rengsirikul K, Ishii Y, Kangvansaichol K, Sripichitt P, Punsuvon V, Vaithanomsat P, Nakamanee G, Tudsri S (2013) Biomass yield, chemical composition and potential ethanol yields of 8 cultivars of napiergrass (*Pennisetum purpureum* Schumach) harvested 3-monthly in central Thailand. J Sustainable Bioenergy Systems 3:107–112
- Shiragami T, Tomo T, Tsumagari H, Ishii Y, Yasuda M (2012) Hydrogen evolution from napiergrass by the combination of biological treatment and a Pt-loaded TiO₂-photocatalytic reaction. Catalyst 2:56–67
- Sluiter A, Hames B, Ruiz R, Scarlata C, Sluiter J, Templaton D, Crocker D (2010) Determination of structural carbohydrates and lignin in biomass, Technical Report NREL/TP-510-42618, National Renewable Energy Laboratory, Golden, CO
- Su R, Ma Y, Qi W, Zhang M, Wang F, Du R, Yang J, Zhang M, He Z (2012) Ethanol production from high-solid SSCF of alkaline-pretreated corncob using recombinant Zymomonas mobilis CP4. Bioeng Res 6:292–299
- Taherzadeh MJ, Karimi K (2007) Enzyme-based hydrolysis processes for ethanol from lignocelluosic materials: a review. BioResources 2:707–728
- Underwood SA, Buszko ML, Shanmugam KT, Ingram LO (2002) Flux through citrate synthase limits the growth of ethanologenic *Escherichia coli* KO11 during xylose fermentation. Appl Environ Microbiol 68:1071–1081
- Utamy RF, Ishii Y, Idota S, Harada N, Fukuyama K (2011) Adaptability of dwarf napiergrass under cut-and-carry and grazing systems for smallholder beef farmers in southern Kyushu, Japan. J Warm Regional Society of Animal Science Jpn 54:65–76
- Yasuda M, Miura A, Yuki R, Nakamura Y, Shiragami T, Ishii Y, Yokoi H (2011) The effect of TiO₂-photocatalytic pretreatment on the biological production of ethanol from lignocelluloses. J Photochem Photobiol A Chem 220:195–199

- Yasuda M, Miura A, Shiragami T, Matsumoto J, Kamei I, Ishii Y, Ohta K (2012) Ethanol production from non-pretreated napiergrass through a simultaneous saccharification and fermentation process followed by a pentose fermentation with *Escherichia coli* KO11. J Biosci Bioeng 114:188–192
- Yasuda M, Takeo K, Nagai H, Uto T, Yui T, Matsumoto T, Ishii Y, Ohta K (2013) Enhancement of ethanol production from napiergrass (*Pennisetum purpureum* Schumach) by a low-moisture anhydrous ammonia pretreatment. J Sustainable Bioenergy Systems 3:179–185
- Yoo CG, Nghiem NP, Hicks KB, Kim TH (2011) Pretreatment of corn stover by low moisture anhydrous ammonia (LMAA) process. Bioresour Technol 102:10028–10034

doi:10.1186/2193-1801-3-333

Cite this article as: Yasuda *et al.*: Bio-ethanol production through simultaneous saccharification and co-fermentation (SSCF) of a low-moisture anhydrous ammonia (LMAA)-pretreated napiegrass (*Pennisetum purpureum* Schumach). *SpringerPlus* 2014 3:333.

Submit your manuscript to a SpringerOpen[®] journal and benefit from:

- ► Convenient online submission
- ► Rigorous peer review
- ▶ Immediate publication on acceptance
- ► Open access: articles freely available online
- ► High visibility within the field
- ► Retaining the copyright to your article

Submit your next manuscript at ▶ springeropen.com